

Pro-Cut®

HP42™ Starter Shingle

Pro-Cut® HP42™ Starter Shingles protect the roof edge and provide anchoring power for high wind resistance at the critical eave and rake areas. They protect the roof by filling in spaces under the cut-outs and edges for the first course of exposed shingles, preventing wind uplift.

PRODUCT SPECIFICATIONS

Product	Exposure	Shingle Dimensions	Per Package
Pro-Cut® HP42™ Starter	Up To 6"	8" x 42"	140 Linear Feet



For maximum protection and warranty coverage, install an Atlas Signature Select® Roofing System with components designed and backed by an Atlas warranty.

FEATURES AND BENEFITS

- Perforated Shingle Design (16" x 42" Shingle. Each yields two 8" x 42" starter shingles per full shingle)
- No need to cut tabs or invert shingles, saving time and labor costs
- FASTAC® Double Sealant Line seal-down strip prevents wind uplift of shingles
- Use with any type of laminate asphalt shingles
- Required with Wind Limited Warranty**
- Increases ice dam protection; ready to install from the bundle
- Atlas Signature Select® Roofing System Eligible¹

ASTM

D3018, Type 1
D3161, Class F, Tested at 110 mph
D3462, As Manufactured

CODES AND COMPLIANCES

Florida Building Code Approved – FL 16305
Miami-Dade County Product Control Approved

SAFETY, STORAGE AND HANDLING

WARNING: Roofing application can be dangerous. Observe all precautions and safety guidelines in accordance with proper roofing trade practices. Minimize roof traffic. Perform regular roof maintenance in appropriate weather.

IMPORTANT PRECAUTIONS: Pallets of Pro-Cut® HP42™ Starter Shingles should not be double stacked. Provide cover on top and sides, allowing for adequate ventilation and store at room temperature until use. Protect from weather during storage and on job site.

For additional safety, storage and handling instructions go to: AtlasRoofing.com/roof-shingles/sds

INSTALLATION AND SPECIFICATIONS

For warranty installation instructions go to: AtlasRoofing.com/roof-shingles/pro-cut-starter-shingles

APPLICATION OF PRO-CUT® HP42™ STARTER SHINGLES

