



technical bulletin

DATE: October, 2014

FROM: Paul Casseri, Product Manager, Residential Roofing Products

SUBJECT: Atlas Pro-Cut Starter Strip Usage

The Atlas **Pro-Cut Starter Strips** are designed to be chosen and used in applications according to the width of the weather exposure of the field shingles to be installed.

- The **6X Pro-Cut Starter Strip** product *is designed to be used with Atlas' or any other manufacturer's asphalt shingles having a weather exposure of up to a maximum of 6" wide.* (This is the standard starter strip typically used with ALL Atlas field shingles except **StormMaster Slate**)
- The **8.5X Pro-cut Starter Strip** is designed to be used with any asphalt field shingles with up to and including an 8.5" weather exposure – and may be used with virtually any asphalt field shingles now available. The **8.5X Pro-Cut Starter Strips** are required to be used with the **StormMaster Slate** shingles.
- The **10X Pro-Cut Starter Strip** is a truly universal starter strip product which can be installed in conjunction with any currently available asphalt shingle with a weather exposure of up to and including 10".

Pro-Cut Starter Strip products are designed to be "**universal**" and can readily be used with **any** manufacturer's asphalt shingles of up to and including the **6X (6") or 8.5X (8.5") or 10X (10")** shingle weather exposure application.

In all installations, the Pro-Cut Starter Strips are to be installed with the sealant line positioned at the eave edge and overhanging the drip edge by approximately $\frac{1}{4}$ " to $\frac{1}{2}$ ".