

Material Name: Saturated Felt Roofing Products

Section 1 - Chemical Product and Company Identification

Product Name(s): Saturated Felt Roofing Products

Chemical Family: Saturated Felt Roofing

Formula: Mixture

Manufacturer:

Atlas Roofing Corporation 2000 River Edge Parkway, Suite 800 Atlanta, GA 30328

Emergency Contacts:

CHEMTREC (24 hours everyday): 1-800-424-9300

CANUTEC (Canada - 24 hours everyday): 1-613-996-6666

Health and Technical Contacts:

Health Issues Information (8am-5pm ET): 1-770-952-1442 Technical Product Information (8am-5pm ET): 1-770-952-1442

Section 2 - Hazards Identification

Global Harmonized System (GHS) Classification:

Health

Eye Irritation – Category 2B (Mild Irritant) Skin Irritation – Category 3 (Mild Irritant)



Respiratory Protection:

A properly fitted NIOSH approved disposable dust respirator should be used when high dust levels are encountered, the level of dust in the air exceeds the OSHA PEL, or if irritation occurs. Use respiratory protection in accordance with your company's respiratory protection program, state and local regulations, and OSHA regulations under 29 CFR 1910.134.

Skin Protection:

A loose fitting, long sleeved cotton shirt, long cotton pants, and gloves are recommended.

Eves/Face Protective Equipment:

Safety glasses or goggles.

Emergency Overview

Breathing dust from this product may cause temporary scratchy throat, congestion, and slight coughing. Getting dust on the skin or in the eyes may cause temporary itching, rash, or redness.

Potential Health Effects

Inhalation: Breathing dusts may cause short term irritation of the mouth, nose and throat.

Skin Contact: Skin contact with dust may cause itching and short term irritation. **Eye Contact:** Eye contact with dust may cause short term mechanical irritation.

Ingestion: Ingestion may cause short term mechanical irritation of the stomach and intestines.

Medical Conditions Aggravated by Exposure: Chronic respiratory or skin conditions may temporarily worsen

from exposure to these products.

Issue Date: 04/17/20 Page 1 of 7



Material Name: Saturated Felt Roofing Products

Section 3 - Composition / Information on Ingredients

Name	CAS Number	Weight %	ACGIH Exposure Limit*	OSHA PEL
Felt (paper)	NA	40-55	10 mg/m ³ (dust)	15 mg/m³ (total) 5 mg/m³ (respirable fraction)
Asphalt	64742-93-4	45-60	0.5 mg/m ³ (fume)	NA

Section 4 - First Aid Measures

Eye Contact:

Do not rub or scratch your eyes. Dust particles may cause the eye to be scratched. Flush with water for 5–15 minutes. If irritation persists, contact a doctor.

Skin Contact:

Wash gently with soap and warm water to remove dust. Wash hands before eating or using rest room.

Ingestion:

Do not induce vomiting. SEEK IMMEDIATE MEDICAL ATTENTION.

Inhalation:

Remove person to fresh air. Drink water to clear throat and blow nose to move dusts.

NOTES TO PHYSICIAN:

None

Section 5 - Fire Fighting Measures

Suitable extinguishing media: There is no potential for fire or explosion. If involved with a fire, use normal fire fighting procedures to prevent inhalation of smoke and gases. Firefighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Firefighters should avoid inhaling any combustion products.

Specific hazards: None.

Special protective equipment for firefighters: None

Flash point: Not applicable

Autoignition temperature: Not applicable

Flammable limits in air - lower (%): Not applicable Flammable limits in air - upper (%): Not applicable

NFPA rating: Flammability: 1 Health: 1 Instability: 0 Other: -

Issue Date: 04/17/20 Page 2 of 7



Material Name: Saturated Felt Roofing Products

Section 6 - Accidental Release Measures

Personal precautions: Pick up large pieces. Vacuum dusts. Do not sweep dry dusts. If sweeping is necessary, use a dust suppressant such as water. These wastes are not hazardous as defined by the Resource Conservation and Recovery Act (40 CFR 261). Comply with state and local regulations for disposal of this product.

Section 7 - Handling and Storage

Handling Procedures:

Comply with all applicable EPA, OSHA, NFPA and state and local requirements. Observe personal protection guidelines of Section 8. Avoid skin contact.

Storage Procedures:

Store product in an area where it will not easily be disturbed or generate dust.

Section 8 - Exposure Controls / Personal Protection

Engineering measures:

Local or general exhaust required in an enclosed area or when there is inadequate ventilation.

Respiratory Protection:

A properly fitted NIOSH approved disposable dust respirator should be used when high dust levels are encountered, the level of dust in the air exceeds the OSHA PEL, or if irritation occurs. Use respiratory protection in accordance with your company's respiratory protection program, local regulations and OSHA regulations under 29 CFR 1910.134.

Skin Protection:

A loose fitting, long sleeved cotton shirt, long cotton pants, and gloves are recommended.

Eyes/Face Protective Equipment:

Wear safety glasses or goggles.

Work Practices:

Handle with good industrial hygiene and safety practices. These include avoiding any unnecessary exposure and removal of the material from the skin, eyes and clothing. Wash hands and arms frequently, shower after exposure and wash work clothes when soiled.

Section 9 - Physical & Chemical Properties

Appearance: Felt (paper) mat saturated with asphalt, packaged in roll form.

Physical state (Solid/Liquid/Gas): Solid Substance type (Pure/Mixture): Mixture

Color: Black

Odor: Slight asphalt odor

Molecular weight: Not determined

pH: Neutral

Boiling point/range (5-95%): Not applicable

Melting point/range: >200 F

Decomposition temperature: Not applicable

Specific gravity: Variable

Density: Variable

Bulk density: Not applicable Vapor density: Not applicable Vapor pressure: Not applicable Evaporation rate: No data available

Solubility: Not applicable

Issue Date: 04/17/20 Page 3 of 7



Material Name: Saturated Felt Roofing Products

Solubility in other solvents: Not applicable

Partition coefficient (n-octanol/water): Not applicable

VOC content (%): Not applicable

Viscosity: Not applicable

Section 10 - Chemical Stability & Reactivity Information

Stability: The material is a stable solid at normal usage temperatures.

Polymerization: Will not occur.

Hazardous decomposition products: The decomposition products from this material are those that would be expected from any organic (carbon-containing) material, and are mainly derived from burning of the resins and binders. These decomposition products may include carbon monoxide, carbon dioxide & carbon particles.

Materials to avoid: None.

Conditions to avoid: Excessive heat, excessive mechanical handling outside the normal usage that would

generate dust.

Section 11 - Toxicological Information

Acute and Chronic Toxicity:

EXPOSURE LIMITS: Reference: "Guide to Occupational Exposure Values 2000, Compiled by ACGIH®"

FELT (PAPER): CAS NA

OSHA: 15-mg/m3 total dust; 5-mg/m3 respirable fraction

ACGIH: 10-mg/m3

NIOSH: 10-mg/m3 total dust; 5-mg/m3 respirable fraction

A: General Product Information

LD50/LC50 For Chemicals, Which May Be Released During Use

B: Component Analysis - LD50/LC50

FELT (PAPER): CAS NA

Chronic Toxicity: No chronic health effects are known to be associated with exposure to paper dust beyond those associated with other dust exposures. Results from epidemiologic studies have not shown any increases in respiratory disease or cancer.

Carcinogenicity:

A: General Product Information

None.

B: Component Carcinogenicity FELT (PAPER): CAS NA: None

Issue Date: 04/17/20 Page 4 of 7



Material Name: Saturated Felt Roofing Products

Section 12 - Ecological Information

Ecotoxicity:

No data available for this product. This product is not expected to produce significant ecotoxicity upon exposure to aquatic organisms and aquatic systems.

Section 13 - Disposal Considerations

US EPA Waste Number & Descriptions:

This material as supplied and by itself, when discarded or disposed of, is not an EPA RCRA hazardous waste according to federal regulations. This material could become a hazardous waste if mixed or contaminated with a hazardous waste or other substance(s). It is the responsibility of the user to determine if disposal material is hazardous according to federal, state and local regulations.

Disposal Instructions:

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Section 14 - Transportation Information

49 CFR 172.101:

DOT:

Transport Information: This material when transported via US commerce would not be regulated by DOT

Dangerous Goods Regulations.

Proper shipping name: Not applicable UN/Identification No: Not applicable Hazard Class: Not applicable

Hazard Class: Not applicable **Packing group:** Not applicable

DOT reportable quantity (lbs): Not applicable.

Issue Date: 04/17/20 Page 5 of 7



Material Name: Saturated Felt Roofing Products

Section 15 - Regulatory Information

US Federal Regulatory Information

US TSCA Chemical Inventory Section

8(b):

This product and/or its components are listed on the TSCA Chemical Inventory.

OSHA Hazard Communication Standard:

This product has been evaluated and determined to be hazardous as defined by the OSHA Hazard Communication Standard due to the potential for mild skin irritation and mild respiratory irritation.

SARA Section 302:

This product contains the following component(s) that have been listed on EPA's Extremely Hazardous Substance

(EHS) List:
None

SARA Section 304:

This product contains the following component(s) identified either as an EHS or a CERCLA Hazardous substance which in case of a spill or release may be subject to

SARA reporting requirements:
None

SARA 311/312

Hazard Classification under SARA 311/312:

Acute Health Hazard: Yes Chronic Health Hazard: No

Fire Hazard: No

Sudden Release of Pressure Hazard: No

Reactive Hazard: No

SARA Section 313:

This product contains the following component(s) that may be subject to reporting on the Toxic Release Inventory (TRI) From R:

None

US State Regulatory Information

State Hazardous Substances Listing

Neither this product nor any of its components appears on any state hazardous substances lists.

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

International Regulatory Information

Canada DSL/NDSL Inventory:

Neither this product nor any of its components is listed

either on the Domestic Substances List (DSL)

WHMIS Status: Not controlled

WHMIS Classification: None

Issue Date: 04/17/20 Page 6 of 7



Material Name: Saturated Felt Roofing Products

Section 16 - Other Information

Key/Legend:

EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; NFPA = National Fire Protection Association; HMIS = Hazardous Material Identification System; CERCLA = Comprehensive Environmental Response, Compensation and Liability Act; SARA = Superfund Amendments and Reauthorization Act; DSL = Canadian Domestic Substance List; EINECS = European Inventory of New and Existing Chemical Substances; WHMIS = Workplace Hazardous Materials Information System; CAA = Clean Air Act

Revision Summary:

This SDS was created on April 17, 2020. Read this information carefully before use of the product.

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental, or consequential damages resulting from its use.

Issue Date: 04/17/20 Page 7 of 7